Orderguide Panthera S3 Swing short

Save the guide to the desktop and open it from there.

art.nr. guide-S3-swing-kort-eng
rev.2022-02

Adjusted by: | Tel:
E-mail: | Date:
Adjusted for:

Total weight (**g**): 0

The weight changes based on the choices made below.

S3 Swing has divided, **swing away leg support** and an adjustable rear axle in carbon fibre. To find a balance that suits you the rear axle can be adjusted into different positions. Note desired measure at "Settings". S3 Swing has a seat height of 45cm in front and 43 cm at the rear, without cushion. To adjust the seat height you can chose other rearwheel sizes or a raising Kit with suitable castor fork from the List of options.
Max userweight: 100 kg for seat width 33-42.

Save the guide to the "desktop" and open it with **Adobe Reader., for best function**
Design your wheelchair by clicking in the circles in this guide.
Blue, underlined text is clickable to show info or image.
BB = seatwidth, **HH**= backrest height

	Original design	Alternative options	Other options (info)
	1) Chassis colour ◯ **Black** - *Anodic Black* ◉ Clear	◯ Optional colour - A higher price and longer delivery time for optional colour, Fili in art.no. in the square	
	2) Seat width (BB) art.no. ◯ **33 cm** ◯ **36 cm** ◯ **39 cm** ◉ Clear		Art.no include: chassis, seat, calf strap, backrest lock
	3) Back rest ◯ S3 standard 523BBHH VER2 ◉ Clear *Height (HH)* ◯ **20 cm** ◯ **35 cm** ◯ **25 cm** ◯ **40 cm** ◯ **30 cm** ◯ **45 cm** ◉ Clear	◯ Tapered 525BBHH VER2 ◯ Curved back 524BBHH VER2	◯ Other back rest art. _____
	4) Rear axle ◯ Carbon standard 33023BB ◉ Clear	◯ Carbon +15 mm 33023BC* * seat width BB +1 Use this rear axle when chosing arm support at Accessories and/or increased seat height	◯ Other rear axle or seat height Increase seat height +0 mm art. _____
	5) Castor and fork ◯ 120 mm art.no. ◉ Clear	◯ 90 mm art.no. ◯ 150 mm art.no.	
	6) Footrest ◯ Swing S3 cpl pair art.no. ◉ Clear	◯ Foot plate large, extended 50mm forward art.no.	◯ Extended tubes 40 mm art.no. ◯ Heel straps for footplates art.no.
	7) Brake ◯ Brake S3 4630000 ◉ Clear		
	8) Rear wheel - *without pushrim* ◯ 22" Standard art.no. ◉ Clear	Rear wheel sizes ◯ 24" Standard art.no. NOTE! Rear axle position only in 0 mm with 24" rear wheels.	◯ Other rear wheel art. _____
	Tire - *choose tire* ◯ Schwalbe Right Run 22", 24" ◉ Clear	◯ Rugged 24" ◯ Schwalbe Marathon Plus 24"	◯ PU 24" (massive) ◯ reTyre-tyre skins (does not fit PU tyres)
	9) Pushrim ◯ Titanium 190DD11 (x2 / wheelchair) ◉ Clear **DD** = Wheel diameter	◯ Paragrip 19051DDBT x2 ◯ Tetragrip 19052DDBT x2	◯ Maxgrip 22", 24"(contains latex) 1903060 x2 (60=24", 80=22") ◯ Aluminum 24" 1904404 x2

Accessories

Side guard S3

○ Side guard S3 Video
art.no.

◉ Clear

Arm support

○ Arm support S3 Video
art.no.

Side guard Carbon

○ Side guard Carbon
art.no.

Push handles

○ Height adjustable S3 Video
4252060 VER2

○ Height adjustable S3 +10
4252063 VER2

◉ Clear

Max. userweight 100kg

Push handle Foldable

○ Foldable S3 Video
4245000

Push bar

○ Push bar S3
42400BB VER2

Max. userweight 100kg

Anti-tip

○ Anti-tip std seat height
4353000 *Video*

Other seat height

Cushion

○ 2,5 cm
572BB35

○ 5 cm
575BB35

◉ Clear

Wedge cushion

○ Wedge cushion
57710BB



Spoke protectors

○ 24" Panthera logo
4500000

○ 24" without logo
4500011

◉ Clear

Other

○ Tube protection front
9900251 (2 pcs)

○ Tube protection rear
9900251 (1 pcs)

○ Crutch holder S3 ____ pcs
9900301 (x1/crutch)

○ Backrest wedge ____ pcs
4710012

○ Table S3
6810020

Set-up adjustments

Backrest angle

Note measure (A) for desired back rest angle.
14-28 mm. Standard=18 mm

A=_____ mm

Rear axle adjustment

Note measure (A) for desired balance.
Standard=25 mm

A=_____ mm

Footrest height

Note measure (A) and (B) for the footrest.

A=_____ mm B=_____ mm

Transportation marking

○ YES do mark the wheelchair with attachment points for transport in disabled service vehicle.

Art.no.9000152

NOTE! See manual for more information.

Extra