Orderguide Panthera U3 Y-front Low - extended range

Save the guide to the desktop and open it from there.

art.nr. guide-U3-Y-front-low-eng
rev.2022-06

Adjusted by:		Tel::	
E-mail:		Date:	
Adjusted for:			

Total weight (g): 0

The weight changes based on the choices made below.

U3 Y-front low has a ajustable rear axle in carbon fibre. To find a balance that suits you the rear axle can be adjusted into different positions. Note desired measure at "Settings". U3 Y-front low has a seat height of 44,5 cm in the front and 41,5 at the rear, without cushion. To adjust the seat height you can chose other rearwheel sizes or a raising Kit with suitable castor fork from the List of options.

Max userweight: 100 kg for seat width 33-42.

Save the guide to the "desktop" and open it with **Adobe Reader., for best function**
Design your wheelchair by clicking in the circles in this guide.
Blue, underlined text is clickable to show info or image.
BB = seatwidth, **HH**= backrest height

Original design	Alternative options	Other options (info)

1) Chassis-colour — Click on the link to see up-to-date colours

Choose colour

2) Seat width *(BB)*
art.no.
◯ 33 cm ◯ 36 cm ◯ 39 cm ◯ 42 cm ◯ 45 cm ◯ 50 cm
◉ Clear

Art.no include: chassis, seat, calf strap, backrest lock

3) Seat depth ◯ 35 cm
art.no.
◉ Clear

◯ 30 cm ◯ 37,5 cm
Only alternative seat at seat width 50 cm

4) Backrest
◯ Standard
523BBHH VER2
◉ Clear

Height (HH)
◯ 20 cm ◯ 35 cm
◯ 25 cm ◯ 40 cm
◯ 30 cm ◯ 45 cm
◉ Clear

◯ Tapered
525BBHH VER2
◯ Curved back
524BBHH VER2

◯ Backrest, extended range
◯ Frame fo fixed backrest systems
art. _____

5) Rear axle
◯ Carbon standard
33023BB
◉ Clear

◯ Carbon +15 mm
33023BC*
* seat width **BB +1**
Use this rear axle when chosing,arm support at Accessories and/or increased seat height

◯ Other rear axle or seat height
Increase the seat height +0 mm

6) Castor and fork
◯ 90 mm
art.no.
◉ Clear

◯ 120 mm
art.no.

7) Footrest *info about footrest height*
◯ Footrest Titanium
36915BB
◉ Clear

◯ Extended, reinforced
36006BB needed for Freewheel
◯ Plastic plate for footrest
36010BB

◯ Other footrest

8) Brake
◯ Brake S3
4630000
◉ Clear

◯ One arm brake, right
art.no.

◯ One arm brake, left
art.no.

9) Rear wheel - *without pushrim*
◯ 24" standard
art.no.
◉ Clear

Rear wheel sizes
art.no.
◯ 24" Spinergy X black spokes
◯ 24" Spinergy X white spokes
◯ 25" Spinergy X black spokes
◯ 25" Spinergy X white spokes
◯ 26" Spinergy X black spokes
◯ 26" Spinergy X white spokes

◯ Annat drivhjul

Tire - *choose tire*
◯ Schwalbe Right Run 24",25",26"
◉ Clear

◯ Rugged 24"
◯ Schwalbe Marathon Plus 24",25",26"
◯ Schwalbe One 24",25"

◯ PU 24" (massive)
◯ reTyre-tyre skins (does not fit PU tyres)

Panthera AB, Gunnebogatan 26, 163 53 Spånga, Sweden - Tel:+46-8-761 50 40, Fax: +46-8-621 08 10, panthera@panthera.se, www.panthera.se

10) Pushrim

- ○ Titanium 190DD11 (x2)
- ◉ Clear

DD = Wheel diameter

- ○ Alu X 24" 1904404 (x2)
- ○ Alu X 25" 1904405 (x2)
- ○ Alu X 26" 1904406 (x2)
- ○ Tetragrip 19052DDBT x2
- ○ Paragrip 19051DDBT x2

DD = Wheel diameter

- ○ Maxgrip 24" (contains latex) 1903060 x2

Accessories

Side guard *

- ○ Side guard S3 Video
  art.no.

* Use sideguard 26" for 24"rear wheels due to the low chassis.

- ◉ Clear

Side guard Carbon

- ○ Carbon
  art.no.
- ○ Carbon, small cover
  art.no.
- ○ Carbon, large cover *
  art.no.

Use sideguard 26" for 24" rear wheels because of the low chassis.
* Only with one arm brake

Arm support *

- ○ Arm support S3 * Video
  art.no.

* Not possible to combine with 25" and 26" rear wheels
Use Arm support 26" for 24" rear wheels due to the low chassis

Push handles H/S

- ○ Height adjustable S3 Video
  4252060 VER2
- ○ Height adjustable S3+10 cm
  4252063 VER2
  Max. userweight 100kg
- ◉ Clear

Push handle Foldable

- ○ Foldable S3 Video
  4245000

Push bar

- ○ Push bar S3
  42400BB VER2

Max. userweight 100kg

Anti tip *low chassis*

- ○ Anti tip std seat height
  4355000 *Video*

Other seat height

Cushion

Seat depth 35cm Seat depth 40cm

- ○ 2,5 cm 572BB35
- ○ 5 cm 575BB35
- ○ 2,5 cm 572BB40
- ○ 5 cm 575BB40
- ◉ Clear

Spoke protectors

- ○ 24" logo
  4500000
- ○ 24" no logo
  4500011
- ◉ Clear

Other

- ○ Tube protection ____p
  9900251 (x3/wheelchair)
- ○ Crutch holder S3 ____p
  9900301 (x1/crutch)
  Video
- ○ Backrest wedge ____p
  4710012

Chose art.no. for Freewheel according to the **footrest height** of the wheelchair Read more about Freewheel on the homepage

- ○ Freewheel Height 6-14 cm art.no. 2600102

Wedge cushion

- ○ Wedge cushion
  57710BB

Set-up adjustments

Back rest angle

Note measure (A) for desired back rest angle.
14-28 mm. Standard=20 mm

A= _____ mm

Rear axle adjustment

Note measure (A) for desired balance.
Standard=60 mm

A= _____ mm

Footrest height *info about footrest height*

Note measure (A).

A= _____ mm

Transportation marking

- ○ YES do mark the wheelchair with attachment points for transport in disabled service vehicle
  Art.no.9000152

NOTE! See manual for more information.

Extra